

BUILDING PRODUCT INFORMATION SHEET

Building Product Information Requirements Regulations 2022



Independent
CERAMICS

Product identification

Product name	ICON COAL SUPERTEC
--------------	--------------------

Physical specifications

Nominal format (cm)	60X60
Thickness (mm, approx.)	9.5
Material	Glazed Porcelain
Surface finish	Supertec
Rectified edges	Yes
Surface slip rating (if applicable)	SRV 57
Weight per m ² (approx.)	21 kg
Box size in pieces	4
Box coverage in m2	1.44
PEI rating	4
Water absorption if known	0.5%
Variation rating	V2 — MODERATE VARIATION <i>This number provides moderate shade and pattern variations. Pieces will vary, yet be similar to each other in colour and/or pattern variations. Each piece of tile may have subtly different colours, patterns, and shades.</i>

Manufacturer and importer details

Country of manufacture	CHINA
Importer name	Independent Ceramics
Importer address	105 Jellicoe Road, Panmure, Auckland 1072
Importer website	www.independentceramics.co.nz
Importer email & phone	admin@indcer.co.nz / +64 9 527 4990

Product scope and intended use

Checked boxed denotes use the product is suitable for, based on testing and manufacturer guidance. **Unchecked** boxes denotes where not suitable or not assessed.

☒ Residential - Wall	☒ Residential - Floor	☒ Commercial - Wall
☒ Commercial - Floor Low Traffic	☐ Commercial - Floor High Traffic Check with project specification.	☒ Within 1.5m of Plumbing Fixture

Building Code obligations

B2 <i>Durability (B2.3.1)</i>	Product must continue to perform for its required durability period when used in accordance to our product scope and intended use guide	☒ Meets requirement ☐ Does not meet requirement
C3 <i>Fire affecting areas beyond source</i>	Relevant where a reaction-to-fire/fire resistance classification applies to the surface finish. Porcelain tile is inorganic and non-combustible;	☒ Meets requirement ☐ Does not meet requirement
D1 <i>Access Routes (D1.3.3)</i>	2.1.2 For level access routes (including level accessible routes) expected to become wet with water in normal use, walking surfaces shall either: a) Have an SRV classification of not less than 39 from the wet pendulum test method of AS 4586 Appendix A using the Slider 96 rubber. Note 2: A slip resistance value of 0.4 when tested under AS/NZS 3661.1 may be assumed as equivalent to a SRV of 39. b) for housing this requirement applies only to the access route on the approach to the main entrance and not inside that entrance and not on the approach to other entrances. The internal access routes of housing, including kitchens and bathrooms, shall be assumed to be dry in normal use.	☒ Meets requirement for level public access routes expected to become wet ☒ Meets requirement for interior use in residential housing ☐ Does not meet requirement for flooring
E3 <i>Internal Moisture (E3.3.2-E3.3.4)</i>	E3/AS1 Water splash areas, floors and walls, lists ceramic or stone tiles with 6% maximum water absorption and waterproof grouted joints as a suitable wet-area floor finish	☒ Meets requirement for watersplash areas ☐ Does not meet requirement

Warning / ban statement

Statement	This product is not currently subject to any warning or ban under the Building Act 2004.
------------------	--

Other relevant information

Relevant information	
-----------------------------	--